

FONTAINE NO-SLACK®

*Industries best defense
against false coupling*

6000LWB

2 inch slide increments

Standard/Moderate duty

50,000 lbs vertical load

150,000 lbs drawbar pull



6000LWB Assembly Features

Fontaine LWB Light Weight Air Slide Bracket

- Only trigger activated fifth wheel system on the market - the industry's best defense against false coupling
- Self-adjusting locking system that provides a No-Slack connection around the trailer kingpin
- Locking system is fully retracted when open which virtually eliminates the possibility of damage to the jaw and wedge
- Steel construction with a larger top surface area for greater strength and stability
- Automatic internal secondary lock
- Pull handle opens easy with a simple straight pull
- Computer-aided bracket design features a smaller footprint with steel reinforcement for strength and durability
- Greaseless bracket liner provides consistent lubrication, reduces wear (no metal-to-metal contact) and cuts maintenance costs
- Two-inch slide increments give you greater versatility for improved payload distribution

6000LWB Performance Option

- **In-Cab Air actuated**— In-cab air release valve located on the dash opens the fifth wheel lock only when the tractor parking brakes are set. Specify code 579-008.



A Marmon |
Berkshire Hathaway
Company



www.fifthwheel.com • 800-874-9780 • Email: parts@fifthwheel.com

©2020 • Fontaine Fifth Wheel LT-251 • R6

Get the app @ [FifthWheel.com/app](https://www.fifthwheel.com/app)

FontaineFifthWheel

@FifthWheelParts

